



## BOWSWIM® Instructions

### 1. General Over View

- A. Bowswim® Deck Plates are most easily installed in pool decks constructed of concrete, or in deck surfaces adhered to a concrete sub-surface. For deck surfaces not adhered to a concrete sub-surface, contact Bowswim for more detailed installation instructions.
- B. For installation in swim spas, contact your swim spa dealer for installation instructions.

### 2. Tools Required For Pool Deck Installation

- A. Power Drill
- B. Masonry Bit: One (1) Inch in Diameter and Six (6) Inches in Length
- C. Hammer
- D. Vacuum
- E. Safety Glasses

### 3. Pool Deck Installation Instructions

Installation requires the use of a power drill. If you are uncomfortable using power tools, it is recommended you contact your pool dealer, or a professional handyman service for assistance.

- A. Consider the configuration of your pool and then determine the best placement of your Deck Plate. Locate it in the shallow end of your pool, six (6) to twelve (12) inches from the edge of the pool deck.
- B. Follow the manufacturer's safety recommendations and precautions for drill use. Use a one (1) inch drill bit and drill a three (3) inch deep hole perpendicular to the pool deck.
- C. Vacuum debris from the hole.
- D. Insert stem of Deck Plate hole and test the fit. If the fit is too tight, gradually enlarge the diameter of the hole to achieve a snug fit. Press down the Deck Plate to seat it in the hole, so that it is flush to the pool deck. Gentle tapping with a hammer may be necessary to seat the Deck Plate. Protect the surface finish of the Deck Plate before tapping it with a hammer.
- E. Insert the bottom end of the telescoping pole into the Deck Plate.
- F. Perform a "pre-exercise warm-up" and begin to enjoy a surprisingly efficient work-out with your new Bowswim.